

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 January 2005 (06.01.2005)

PCT

(10) International Publication Number
WO 2005/001496 A1

(51) International Patent Classification⁷: **G01R 33/28**

(21) International Application Number:
PCT/GR2004/000037

(22) International Filing Date: 29 June 2004 (29.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20030100282 30 June 2003 (30.06.2003) GR

KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: PAPPAS, Panagiotis, T. [GR/GR]; 26, Markopoulioti Street, GR-11744 Athens (GR).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND MEANS OF MULTI-ACTIVATION OF IONS AND ATOMS WITH NMR AND EPR.



(57) Abstract: The invention uses one inductor, which is comprised of one, two or few twisted or parallel conductors and exposes the sample in a pulsed and damped alternating magnetic field B without necessarily the employment of a second constant intensity magnetic field. In this way, the nuclei and the electrons of the sample-object are activated, in the presence of a non-constant magnetic field B that gets infinite negative and positive values between successive damped positive and negative values, crossing through the zero value during a magnetic pulse. Thus, a wide nuclear NMR and Electronic EPR Multiple - Resonance of sample, is achieved.

WO 2005/001496 A1

Method and Means of Multi-Activation of Ions and Atoms with NMR and EPR.

Dr. Panagiotis Pappas, Professor of Physics, Professor of Mathematics.

Introduction:

The method of Nuclear Magnetic Resonance (NMR) for the Atomic Nucleus and of the Electron Paramagnetic Resonance (EPR) for the Atomic Electrons respectively, consists in the use of two geometrically vertical magnetic fields. The intensity of one of them is kept constant, and is usually in the order of 2 Tesla, as in NMR Imaging.

The intensity of the second magnetic field is pulsed and its aim is to divert the already oriented on the constant magnetic field atomic nuclei (or electrons), which returning to their previous state emit the absorbed energy in the form of radiated electromagnetic energy. The frequency of the said electromagnetic energy depend on the intensity B of the applied constant magnetic field, $\Delta E = h\nu = \gamma B\hbar/2\pi$, from the acoustic frequencies band, up to the microwaves band, cf. W. Atkins Physical Chemistry Book, Oxford University Press, 1994, Fifth Edition, p. 625.

Two main applications of Nuclear Magnetic Resonance are NMR spectroscopy and Magnetic Representation (Nuclear Magnetic Resonance Imaging NMRI or more widely known as MRI) otherwise known in Medicine as Magnetic Diagnostic Tomography. With the technique of Nuclear Magnetic Resonance, a sample is placed in a constant intensity B magnetic field and is exposed to the pulses of a second magnetic field. After the pulse emission pause, the response echo is recorded from the sample and analyzed. Bibliography: Nuclear Physics K. Alexopoulos, Athens 1967, Magnetism in Medicine, edited by Andra and Nowak, Wiley 1998, Scientific American, February 1968.

The phenomenon of gyroscopic precession.

The phenomenon of gyroscopic precession for gyroscope is caused by an off-centre force, which, nevertheless, does not accomplish a complete re-orientation. In order for the gyroscope to maintain the general orientation in space, it follows a precession around the axis of its initial orientation. Thus, on an average, the gyroscope maintains the original direction of its rotation axis. This phenomenon is named "the natural precession of the gyroscope".

Generally, the electrons and the protons are gyroscopes that is they possess angular momentum J and magnetic momentum, M, spin, namely, they are magnets.

They can be considered annular gyroscopes (circular orbits) of closed electrical currents, loops, which possess angular momentum J and magnetic momentum M. They also possess charge $q = \pm e$ and mass, m, that is to say they are characterized by m, q, J, M and can be considered as Electric and Magnetic rotating Gyroscopes.

The Frequency of Precession of a gyro is usually much - much smaller than the frequency of their rotation. This also applies to the frequency of precession of protons-electrons.

- When the Protons and the electrons precess, as described above, they can emit radio waves of relatively low frequency, and can return to their original (spin), without precession. These radio waves are the basis of magnetic resonance that come from NMR and EPR and that (NMR) is the basis of NMRI, which is used in medicine for diagnostic purposes. Obviously, the protons - electrons rotating magnetic gyroscopes - are very easily disturbed and can begin to undergo a precession, after the sudden presence of a magnetic field or a magnetic pulse, in the presence of another restoring magnetic field. This observation is the basis of the present invention described below:
- The first fundamental objective of the present invention is the NMR and EPR multiple-resonance. To achieve this aim it employs only one inductor (coil) which is comprised of a coil of one, two or few turns of twisted or parallel conductors instead of the two magnetic fields of the known methods NMR and EPR, thus exposing the sample to a pulsed and damped-wave alternating magnetic field B without the use of a second constant intensity B magnetic field. Thus activating the nuclei and the electrons of a sample object, in the presence of the magnetic field of the Earth and in the presence of a non-constant magnetic field B that repeats infinite negative and positive values between a maximum positive absolute value and zero intensity during each magnetic pulse (around 10 to 50 microseconds).
- In this way, a wide nuclear NMR and electronic EPR multiple-resonance of the sample is achieved, according to the law: $\Delta E = h\nu = \gamma B h / 2\pi$, see W. Atkins Physical Chemistry Book, Oxford University Press, 1994, Fifth Edition, p. 625, with B variable where B is the resultant of the magnetic field of the Earth field and of the damping oscillation of the applied coil.
- The effect of magnetic pulses on biological matter, outside and around the cells of organisms, is generally known in the medical world. The present method as well as the previous invention 1001784/6/21995/OBI of the inventor are able to effect NMR, EPR and to induce electric charges, ion concentrations or concrete atoms, inside organic or inorganic matter, inside biological matter, or inside any kind of matter in which exist movable electric charges or atoms, for which however an exceptionally high impetus is required in order to overcome the high potential barrier existing on both sides of the cellular membrane.
- As it was reported above, the present invention can also cause multi - NMR and EPR.
- The present method employs a device that in the presence of the ambient magnetic field of the Earth or not, produces a damped magnetic field with the help of discharges via any electronic arrangement of conductivity switches, either electronic, or an otherwise equivalent switch arrangement, for example a plasma discharge, that can be suitably activated by any "external" means, i.e. any sort of trigger arrangement or by self-activated avalanche effect.
- The exposed method and device produce a damped magnetic field that possess the characteristics of maximum instantaneous power and very small temporal duration which result from an electric arrangement of a large capacity and, at the same time, of small self-induction and almost zero output load.

The use of damped alternating magnetic fields also causes induced electrical tension in a single surface loop or volume (induction in a one turn coil), at most equal in the order of magnitude to the initial electrical tension of the source that alters the magnetic flow.

In order to achieve the above described results from a distance, which will be comparable with the above magnitudes and to be practically feasible, the present method employs arrangements of switches, that can be of any type from the known types of semiconductors, or plasma discharge switches, as the plasma oscillations which had been employed for this purpose and which have been observed in electrical discharges through various gases, as it has been reported with the previous invention.

This new method is also ideal for the supply of electric currents in medicine by induction, where electric circuits can be formed between cellular regions, without the need for the inevitable invasion or for some form of surgery in order to achieve electrode contact. It is also suitable for the activation of the atomic nuclei because of the phenomenon of Nuclear Magnetic Resonance NMR and respectively for the electrons of atoms because of the phenomenon of Electron Paramagnetic Resonance EPR, that can lead to Biological Nuclear transmutations, see Louis Kervran Biological Transmutations ©1972 Swan House Publishing Co.

The method is applied without the need for physical contact, even over clothes and it can penetrate in-depth proportional with the intensity level employed, because it is known that the magnetic field can effectively act from a distance and particularly through biological tissue.

It has also been observed that the magnetic field can achieve catalysis of chemical reactions, see bibliographic reports:

M. YAOITA, T. WADA et al., Electrochemical study of enzymatic reaction of glucose oxidase in magnetic fields Abstract: 17th ann Mtg. BEMS, Boston, Mass., June 1995.
W. HABERDITZL Enzyme activity in High magnetic fields. Nature 7 January 1967, p73 (1967).

A.S.M. I. NAZAR, a PAUL et al., Frequency dependent alteration of enolase activity by electric, magnetic and combined EM ELF Fields Abstract: 17th Annual Mtg. BEMS BostonMass, June 1995.

S. COMOROSAN, S. VIERU & P. MURGOCI The effect of electromagnetic field on enzymic substrates. Biochim. Biophys. Acta. 268,620 - 621.1972).

E.S. COOK & M.J. SMITH Increase in Trypsin activity in Biological Effects of magnetic fields, pp246-254, Plenum Press, NY, 1964

The present method has various other applications without the need for direct electrical contact, whenever the activation of specific atoms, nuclei, ions or charges, formation of selected chemical compounds, nuclear transmutations, (e.g. according to Kervran) are required.

That is, we have the promotion of a catalytic action or activation (nuclear) from a distance that maintains, accelerates or initiates a potential chemical or nuclear reaction that otherwise would not happen or would proceed with a very slow rhythm.

An embodiment of the method becomes apparent from the following sample of the so called PAPIMI device. (PAPIMI stands for Pappas Ion Magnetic Induction) device that is pictured in figures 1, 2a, 2b, 3a, 3b, 4a, 4b, 5. The PAPIMI device operates in the ambient

magnetic field of the Earth with its induction coil held (21), (21a) held preferably with its axis perpendicular to the ambient magnetic field (of the Earth), and consists of a power supply cord (1) figure 1, that provides electrical energy 230 Volts, 50/60 Hz to the control unit (2) figure 1, a switch, timer switch and a switch regulated output transformer of 30 Kilovolts, from a unit (4) figure 1 which is connected via high electrical tension lines (3) figure 1 with the high tension transformer's output of the unit (2) figure 1. The unit (4) figure 1 rectifies the transformer's high tension. The high tension charges via the high tension lines (5) figure 1 and contacts A and B energy reservoir (7), figure 2a, 2b which is a 0,05 μ F capacitor and 50 Joules energy storage capacity and has a great speed of discharge, which results in very high power discharge in the order of Giga-Watts. The energy reservoir is connected to the high tension and high current carrying capacity line (6A) figure 2a, 2b with, either the electronic switch arrangement (14) figure 2a, or with any other equivalent switch, i.e. plasma discharge switch (14) figure 2b.

Specifically, this switch arrangement (14) figure 2a, 2b, is constituted of a suitable electronic arrangement either of:

a) One or more semi conductive elements switch, (14) which are connected with one of the two leads of the connection box (16) figure 2a.

One terminal of the connections box (16) figure 2a is connected with the one terminal of the energy reservoir (7) figure 2a; via the high current and intensity line (6B) figure 2a. Line 6A connects the other terminal of the energy reservoir (7) figure 2a with the other end of said semi conductive elements (14) switch to the capacitive energy storage bank. Capacitive energy storage bank is connected via leads (5) through connection points (A) and (B) with the high-tension power supply unit.

Inductor (22) figure 2a, 3a, 3b is connected to the connection box (16).

Or b) Any other equivalent switch i.e. a plasma discharge switch, (14) which is connected to the energy reservoir (7) figure 2b via Line 6A and also with the one of the two leads of the connection box (16) figure 2b.

The other lead of the connection box (16) figure 2b is connected to the other terminal of the energy reservoir (7) figure 2b via the high tension and high current carrying capacity flexible line (6B) figure 2b.

Said plasma discharge switch, (14) is connected via leads (5) through connection points (A) and (B) with the high-tension power supply unit.

Similarly, inductor (22) figure 2a, 3a, 3b is connected to the connection box (16).

The inductor (22), figure 3a, 3b, 4a, 4b, consists of the transport line (18) with specifications for very high power, very high electrical tension and very high current carrying capacity, and is surrounded by a cylindrical, high tension withstanding insulation (17) figure 3a, 3b, 4a, 4b. Finally, the inductor's transport line (18) figure 3a, 3b, 4a, 4b connects the inductive coil which is comprised of one, two or few twisted (21a) figure 3b, or parallel conductors (21) figure 3a, that is placed inside the ring's (20) figure 3a, 3b high-tension insulation. The cylindrical insulation (17) figure 3a, 3b, 4a, 4b and the overall ring constitute a waterproof concave body, as they are portrayed in figures 3a, 3b, 4a and 4b, in order to provide proper insulation and protection for the objects they surround, without blocking the exit of magnetic lines (23) figure 4a, 4b from the ring (20) figure 3a, 3b, 4a, 4b. Under the ring (20), exhibit (24) is placed at a distance preferably no greater than the ring's diameter.

The invention operates as follows: After the energy's reservoir capacitor (7) figure 2a, 2b electrical tension is increased beyond a critical value, then either the electronic switch arrangement (14) figure 2a, or any other equivalent switch e.g. a plasma switch (14) figure 2b is fired, that can by suitable activation or by self-activation of the avalanche effect, thus becoming conductive, which results in the creation of a damped wave oscillating electrical current.

The damped and oscillating electric current, as portrayed in the oscillogram of figure 5 in the electronic switch arrangement (14) figure 2a or in any other equivalent switch i.e. plasma discharge switch (14) figure 2b, is channeled to the inductor (21) figure 3a, 3b. The inductor (21) which is comprised of one, two or few coil turns of twisted (21a) or parallel (21) conductors figure 3a, 3b 4a, 4b produces a similarly altered with the electric current oscillations magnetic field flow.

After the discharge of the last pulse from the unit (4) figure 1, after the firing of the electronic switch (14) figure 2a or any other equivalent switch e.g. a plasma discharge switch (14) figure 2b, and after the first pause, the reservoir-capacitor (7) figure 2a, 2b is practically empty. During the pulsations pause of the unit (4) and without any available electric power, the conductivity of the switch is suspended.


Arrangement (14) figure 2a, 2b becomes once again non-conductive, giving opportunity for the reservoir (7) figure 2a, 2b to be recharged again by the unit (4) to the highest critical electrical tension and then for a new conductivity firing to occur. The cycle is then repeated, in the same way as before.

Under inductor coil which is consisted of one, two or few twisted (21a) figure 3b or parallel (21) figure 3a conductors the similarly altered magnetic flow (23) figure 4a, 4b intercepts exhibit (24) figure 4a, 4b. In the presence of an ambient magnetic field or not, nuclear and electronic spins (25) are reoriented in exhibit (24) and they are causing multi - NMR and EPR, (26), (27), (28) figure 5 (because of the variability of the magnetic field intensity B), ions are induced and, electrical charges are moved in general. Elements whose resonant frequency coincides with the frequency that corresponds to the formula $h\nu = \gamma B \hbar / 2\pi$, or to the induced current frequency, absorb the highest amount of energy.

The damped wave form of energy of this method, allows the instantaneous power of these oscillations to be much greater than the average power. Also, the NMR echo signals are delayed, a short time after the main damped wave oscillating pulse "hits" the sample (26), (27), (28), figure 5.

Thermal effects (which are proportional to the average power of the oscillations) are limited, while phenomena that depend on impactive (immediate) value of electrical tension are increased, i.e. NMR and EPR are enhanced (26), (27), (28), figure 5, or the rendering of chemical reactions is increased, which when they are exposed to the device's magnetic induction in order to take place, require an electrical "push" above a high critical value. A specific example of this is the movement of electric charges through the cellular membrane.

Another example of NMR is the activation of sodium Na and oxygen O nucleus, so as to allow the thermonuclear reaction Kervran - Pappas to take place:



That is, the activation of nuclei takes place, and consequently so do nuclear reactions via Nuclear Magnetic Resonance.

In this way, by selecting a suitable electrical characteristic switches arrangement (14), figure 2a or 2b, a suitable self induction L around 1 μ H for the inductor), which is comprised of one, two or few twisted (21a) figure 3b or parallel (21) figure 3a conductors a sufficiently high electrical tension for the power supply and a suitable frequency for the pulses produced by the unit (4) figure 1, an inductive oscillating tension in the exhibit (24) figure 4a, 4b, can be achieved, which is characterized by a specific resonant frequency, or resonant frequencies spectrum.

Due to the fact that there is not enough time between two cycles of operation, for the activated nuclei to get de-activated, the quantity of exhibit's (24) figure 4a, 4b activated nuclei (25) and /or electrons (25) figure 4a, 4b and (26), (27), (28), figure 5 increases after the repetition of each operational cycle of the device, that is, by repeating the inductor (21) figure 3a, or (21a) figure 3b, current feeding after each new charging of the energy reservoir-capacitor (7) figure 2a, 2b. The end result in exhibit (24) figure 4a, 4b is a function of the magnetic field's intensity and the device's operation time.

Concerning specific applications of this method for ion transport or chemical and nuclear reactions initiation, to which specific atoms nuclei or electrons react or are being transported, apart from inventor's previous invention 1001784/6/21995/OBI, no other method is known.

The present new method is important because it does not require intervention or entry into exhibit (24) figure 4a, 4b, (e.g., using electrodes and/or chemical substances), and because the induced electrical tension is momentarily very powerful, because of the conductivity oscillations of the electronic switch arrangement (14) figure 2a or of the plasma switch (14) figure 2b, without the requirement for the initial power supply tension to be equally as big.

Like the inventor's previous invention # 1001784/6/21995/OBI, the expected applications of the present invention are similarly extended to a great technological and scientific spectrum, where NMR and EPR, locomotion of charges, ions, nuclei and specific atoms in inaccessible regions is required, for illustration in Biology, Medicine, Chemical Industry, Nuclear Industry for selective energy supply to Chemical and Nuclear reactions, initiation at will of Chemical-Nuclear reactions, control of Chemical-Nuclear reactions, catalysis of chemical reactions for the supply of selected products between various other products, which cannot possibly be separated with other methods of energy supply, and the activation of exhibits with the Nuclear Magnetic Resonance (and/or Electron Paramagnetic Resonance) (26), (27), (28), figure 5 as it is employed today in the field of Diagnostics Medicine with great success and effectiveness, the Nuclear Magnetic Resonance phenomenon which is also based on the selective energy absorption by the atomic nuclei.

With this described method, electromagnetic radiation ($\sim 1/r^2$) is not produced to the greater percentage of the field's energy, because the intensity of the produced field weakens very fast ($\sim 1/r^3$) where r is the distance from the coil (21) figure 4a, 4b.

The intensity of the field is that of a magnetic dipole, inversely proportional to the third power of the distance ($1/r^3$), a fact that indicates that the field's influence does not extend to a substantial distance and is not radiated according to $1/r^2$ law.

The produced field frequency can be outside the microwave band frequencies (being smaller), with good results.

Obviously, a variation of the proposed device-embodiment of the method described above, can also be materialized by, nevertheless, using a second auxiliary magnetic field to assist or to contribute together with the ambient Earth's magnetic field, in restoring the disturbed (under precession as described above) spins of nucleus and spins of electrons. Also, note, this second auxiliary field can be used as substitute for the Earth's magnetic field, in part or in all, or this field can be used, being actually redundant, just for the sake of a novelty, with the device producing the same results as described above.

Appendix : Calculation of the Kervran – Pappas nuclear reaction energy.

In order to calculate the energy exchange of the Kervran – Pappas reaction, the exact atomic masses for the related isotopes of Na, O, K from the "HANDBOOK of CHEMISTRY and PHYSICS" 82-nd Edition © 2001 by CRC Press LLC, Section 11, page-52, 59.) are employed.

The evolution of the Atomic Energy from the said reaction, is calculated by the formula : $E=mc^2$

A) for Sodium atoms : $\text{Na}^{23} = 22,989769700000$: 100% natural abundance, because there is only one isotope in nature.

B) for Oxygen atoms : Isotope $\text{O}^{16} = 15,99491462200$ (99,757%), leading to $\text{K}^{39} = 38,963706900000$ - natural abundance: 93,2581%

Isotope $\text{O}^{17} = 16,999131500000$ (0,038%), leading to $\text{K}^{40} = 39,963998700000$ - natural abundance: 0,0117%

Isotope $\text{O}^{18} = 17,999160000000$ (0,205%), leading to $\text{K}^{41} = 40,961826000000$ - natural abundance: 6,7302%

Thus the mean mass for O = 15,999404927439

C) for Potassium atoms :

K mean value from above = $38,9637069 \times 99,957 + 39,9639987 \times 0,038 + 40,961826 \times 0,205 = 38,968182$

K books' mean value = 39,098300000000

D) : Mass changed unto Energy :


For O^{16} : $\text{DM} = 22,9897697 + 15,994914622 - 38,9637069 = 0,000020977422$ Kgr/Mol (SI Units) 99,757%


For O^{17} : $\text{DM} = 22,9897697 + 16,9991315 - 38,969987 = 0,00002490125$ Kgr/Mol (SI Units) 0,038%

For O^{18} : $\text{DM} = 22,9897697 + 17,99916 - 38,9681823 = 0,0000271037$ Kgr/Mol (SI Units) 0,205%

Which, using $E=DMC^2$, $C = 299792458$ m/s for the velocity of light, leads to exothermic (giving out energy) reactions for Na and all Isotopes of O, as follows:

E) PAPPAS' EXOTHERMIC NUCLEAR REACTIONS BY ISOTOPE :





F) Conclusion : Mean energy released: ${}_{11}\text{Na} + {}_8\text{O} = {}_{19}\text{K} + 452.787 \text{ Kcal/mMol}$

5

SHORT DESCRIPTION OF THE DRAWINGS

Figure 1:

- 5 The present block diagram shows the control unit (2) that includes a start - stop operation switch, timer and the rectification, electrical filtering and electrical current restriction unit (4), and its aim is to produce the flow of electrical energy from the main power supply to the switch circuitry arrangement and output coil - probe.

Figure 2a :

- 10 The present drawing shows the basic probe input circuitry with electronic switch or other switch arrangement (14), which controls the discharge of the energy reservoir (7) stored in the inductor - probe (22).

Figure 2b :

- 15 The present drawing shows an equivalent modification arrangement of another equivalent circuitry of 2a.

Figure 3a:

- 20 The present drawing shows the inductor (22) which consists of the transport line (18) with its insulation (17) and the insulated ring (20) in which the inductive coil (21) which is comprised of one, two or few parallel conductors (21) that produce a variable intensity magnetic field is found.

Figure 3b:

- 25 The present drawing shows the inductor (22) which consists of the transport power line (18) with its insulation (17) and the insulated ring (20) in which the inductive coil (21a) which is comprised of one, two or few twisted conductors (21a) that produce a variable intensity magnetic field is found.

Figure 4a:

- 30 The present drawing shows the inductor (22), which consists of the transport power line (18) with its insulation (17) and the insulated ring (20) in which the inductive coil (21) which is comprised of one, two or few twisted (21a) or parallel (21) conductors is found, that produces a variable intensity magnetic field (23), in which biological material is exposed (24), that, in this particular case, is a human body.

Figure 4b:

- 40 The present drawing shows the inductor (22) that consists of the transport power line (18) with its insulation (17) and the insulated ring (20) in which the inductive coil (21) which is comprised of one, two or few twisted (21a) or parallel conductors (21) that produces a variable intensity magnetic field (23), is found and in which any material (24) can be exposed. Also shown are nuclei or protons or electrons with a random spatial orientation, the magnetic spin vectors of the atomic nuclei (25) and/or electrons of exposed material (24) atoms (25).

Figure 5:

Oscillogram of the NMR effect produced by an actual device, using only one induction magnetic field, and in the presence only of the magnetic field of the Earth, and embodying the presently described method.

- 5 The NMR sample response is portrayed as the "spike" – peak intense signal (26), (27), (28). "X" axis represents time domain. "Y" axis represents relative field amplitude. Notice: NMR traces are shown towards the end the of event. They are delayed some time after the main damped wave oscillating pulse first "hits" the sample and appear as an echo, as correctly expected by the known NMR relaxation.

10

CLAIMS.

The present invention, refers to:

- 5 1. A method that employs one magnetic field (23) figure 4a, 4b in the presence of the magnetic field of the Earth, and one inductor which is comprised of one, two or few twisted (21a), figure 3b or parallel (21), figure 3a conductors that is supplied by an electronic switch arrangement (14) figure 2a with possible use of semiconductors and/or other types of electronic arrangements, or any other equivalent switch i.e. plasma switch
 10 (14) figure 2b, with the least possible self induction: $< 10 \mu\text{H}$, a great and sudden current: $> 10000 \text{ A}$, small total duration: $< 0.1 \text{ ms}$, and causes any of the following :
 I. Magnetic Nuclear Multiple - Resonance and Nuclear (25) figure 4b activation of exhibits' atoms (24) figure 4a, 4b, and (26), (27), (28) figure 5 with possibility of initiation of Nuclear reactions.
 15 II. Electronic Paramagnetic Multiple - Resonance and Activation of Electrons (25) figure 4b of exhibits' atoms (24) figure 4a, 4b and (26), (27), (28) figure 5 with the possibility of initiation of Chemical changes.
 III. Every possible combination of the above, where the absorption of energy by matter is presented as a general characteristic, with consequential changes from their former state.
 20 IV. Oscillation or locomotion of atoms, nuclei (25) figure 4b, electrons (25) figure 4b, ions, electric charges with the accompanying creation of electrical currents or not.
2. A preferred embodiment for the above described method, consisting of an inductor which is comprised of one, two or few twisted (21a), figure 3b or parallel (21) figure 3a
 25 conductors.
3. An Appliance characterized by a suitable power supply (2), (4) figure 1, that supplies a capacitor - reservoir (7) figure 2a, 2b, faculty of attribution of an electrical power, which is connected to an electronic switch arrangement (14) figure 2a, or to any other equivalent switch
 30 e.g. a plasma switch (14) figure 2b, which can be suitably activated or self-activated and into which electrical conductivity is caused and this electrical conductivity produces very powerful and characteristic (of the electronic switch arrangement (14) figure 2a) or any other equivalent switch i.e. plasma switch (14) figure 2b), electrical oscillations that lead to an inductor which is comprised of one, two or few twisted (21a) figure 3b or parallel (21) figure 3a conductors,
 35 and exposes with damped wave alternating magnetic field (23) figure 4a, 4b oscillations, materials (24) figure 4a, 4b, biological matter, human or animal bodies with any of the following resulting products:
 Magnetic Nuclear Multiple - Resonance, (26), (27), (28), figure 5, Electronic Paramagnetic Multiple - Resonance, (26), (27), (28) figure 5 oscillation or locomotion of
 40 atoms, nuclei (25) figure 4b, electrons (25) figure 4b, ions, electric charges, etc, that are reported in claim 1.
4. A Variation of the said method and apparatus which uses a second induction field contributing together with the ambient magnetic field of the Earth or substituting it in part or in all, and which
 45 apparatus produces the characteristic field of claim 1 by an electronic switch arrangement (14) figure 2a or of any other equivalent switch i.e. plasma switch (14) figure 2b, that use the characteristic oscillations of electronic switch arrangement (14) figure 2a or of any other equivalent switch i.e. plasma switch (14) figure 2b for the production of a pulsating, damped wave magnetic field (23) figure 4a, 4b with the products reported in claims 1 and 3, and generally

industrial or non-industrial products, based on the NMR and EPR Multiple – Resonance (26), (27), (28), figure 5.

1/8




Figure 1

2/8




Figure 2b

3/8




Figure 2a

4/8




Figure 3a

5/8




Figure 4a

6/8




Figure 4b

7/8




Figure 3b

8/8




Figure 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GR2004/000037

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G01R33/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02/056047 A (OXFORD INSTRUMENTS SUPERCONDUCTIVITY LIMITED) 18 July 2002 (2002-07-18) page 17, line 30 - page 18, line 4	1-3
A	EP 0 823 639 A (OXFORD INSTRUMENTS LIMITED) 11 February 1998 (1998-02-11) the whole document	1-4
A	WO 97/13159 A (OXFORD INSTRUMENTS) 10 April 1997 (1997-04-10) the whole document	1-4

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

S document member of the same patent family

Date of the actual completion of the international search

29 October 2004

Date of mailing of the international search report

05/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Volmer, W

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GR2004/000037

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 02056047	A	18-07-2002	EP 1352258 A1	15-10-2003
			WO 02056047 A1	18-07-2002
			US 2004066194 A1	08-04-2004
<hr/>				
EP 0823639	A	11-02-1998	EP 0823639 A1	11-02-1998
			JP 10229977 A	02-09-1998
			US 6072315 A	06-06-2000
<hr/>				
WO 9713159	A	10-04-1997	EP 0819257 A1	21-01-1998
			WO 9713159 A1	10-04-1997
			JP 10510631 T	13-10-1998
			US 6002256 A	14-12-1999
<hr/>				